

SPRAY GUN AND SET UP DATA SELECTOR: Gun Inlet Pressure 2.0 bar/29 psi



PRI Filler/Primer Gun



GTi Topcoat Gun



GTiW Basecoat Gun



SRi Spot Repair - Topcoats



SRiW Spot Repair - Basecoats

| Air Cap No: | | 310 (Trans-Tech) | 110 (Trans-Tech) | 115 (HVLP) | 210 (Trans-Tech) | No 215 (HVLP) |
|---------------------|--|------------------|------------------|-------------|------------------|---------------|
| PRIMERS & SEALERS | Delfleet chromate-free Wash Filler F 393 | 1.6 mm | Use PRi Gun | Use PRi Gun | 0.8 mm | Use SRi |
| | SOLVENTBORNE BASECOAT | | | | | |
| WATERBORNE BASECOAT | Deltron Filler 2K MS Prima D839 /2K HS D8022 /2K UHS D8023 | 1.8 mm | Use PRi Gun | Use PRi Gun | 0.8 mm | Use SRi |
| CLEARCOATS | Deltron DG /Deltron UHS Filler D 825 -K 93 Wet on Wet | Use GTi Gun | 1.4 mm | Use GTi Gun | 0.8 mm | Use SRi |
| | Deltron Basecoat | Do Not Use | 1.3 mm | 1.3 mm | 0.8 mm | 0.8 mm |
| | Deltron Envirobase | Do Not Use | 1.3 mm | 1.3 mm | 0.8 mm | 0.8 mm |
| | 2K MS /HS Clearcoat D800 /D880 /D893 / D894 | Do Not Use | 1.3 mm | Use GTi Gun | 0.8 mm | 0.8 mm |